

Serial No.: 10/533,601
Examiner: Hossein Kafimosavi
Reply to Office Action Mailed June 11, 2008
Page 2 of 8

RECEIVED
CENTRAL FAX CENTER

DEC 11 2008

Amendments to the Claims:

This listing of claims will replace all prior versions, and listing, of claims in the application.

1. (Canceled)
2. (Currently amended) The analytical tool according to claim 18 ~~[[1]]~~, further comprising a substrate, a cover bonded to the substrate and defining the capillary together with the substrate, and a working electrode and a counter electrode which are formed on the substrate and which include respective exposed portions facing interior of the capillary;
wherein at least part of the window is formed at a region which avoids a position directly above the ~~exposed portions~~ second end of the second electrode.
3. (Currently amended) The analytical tool according to claim 2, wherein entirety of the window is formed at a region which avoids a position directly above the ~~exposed portions~~ second end of the second electrode.
4. (Currently amended) The analytical tool according to claim 3, further comprising an air vent for discharging air from the capillary;
wherein the window is provided between the air vent and a ~~downstream one the~~ second end of the second electrode in the ~~of the exposed portions in a flow direction of~~ the sample liquid.
5. (Currently amended) The analytical tool according to claim 4, wherein the window includes an a most-upstream edge which is aligned with a downstream edge of the second end of the second electrode point which corresponds to or generally ~~corresponds to a most downstream point of the downstream one of the exposed portions~~ in a thickness direction of the substrate.

Serial No.: 10/533,601
Examiner: Hosein Kafimosavi
Reply to Office Action Mailed June 11, 2008
Page 3 of 8

6. (Currently amended) The analytical tool according to claim 18 ~~[[1]]~~, further comprising a substrate, a cover bonded to the substrate and defining the capillary together with the substrate;

wherein the window is provided by forming a transparent portion in the cover and forming an opaque portion around the transparent portion.

7. (Original) The analytical tool according to claim 6, wherein the cover comprises a transparent member, and an opaque layer formed with an opening and laminated on a surface of the transparent member;

wherein the window is defined by the opening.

8. (Original) The analytical tool according to claim 7, wherein the opaque layer is provided by forming a film directly on the surface of the transparent member.

9. (Currently amended) The analytical tool according to claim 7, wherein the opaque layer comprises a ~~thin~~ film bonded to the surface of the transparent member.

10. (Original) The analytical tool according to claim 6, wherein the cover includes an opaque member formed with an opening, and a transparent member embedded in the opening; and

wherein the window is provided by the transparent member.

11. (Currently amended) The analytical tool according to claim 18 ~~[[1]]~~, wherein the opaque region has a color which presents a high-contrast with a color of the sample liquid.

12. (Original) The analytical tool according to claim 11, wherein the sample liquid is blood or urine.

Serial No.: 10/533,601
Examiner: Hosain Kafimosavi
Reply to Office Action Mailed June 11, 2008
Page 4 of 8

13. (Currently amended) The analytical tool according to claim 18 ~~[[1]]~~, further comprising an additional window for checking whether ~~that~~ introduction of the sample liquid into the capillary is started.

14. (Currently amended) The analytical tool according to claim 13, further ~~comprising a working electrode and a counter electrode which are formed on the substrate and which include respective exposed portions facing interior of the capillary;~~
wherein at least part of the additional window is formed at a region which avoids a position directly above the first end of the first electrode ~~exposed portions~~.

15. (Currently amended) The analytical tool according to claim 14, wherein entirety of the additional window is formed at a region which avoids a position directly above the first end of the first electrode ~~exposed portions~~.

16. (Currently amended) The analytical tool according to claim 15, wherein the additional window is provided between the sample liquid introduction port and the first end of the first electrode in the ~~an upstream one of the exposed portions in a flow~~ direction of the sample liquid.

17. (Original) The analytical tool according to claim 16, wherein the additional window is provided adjacent to the sample liquid introduction port.

18. (New) An analytical tool comprising:
a substrate,
a cover bonded to the substrate,
a capillary formed between the substrate and the cover for moving a sample liquid from a sample liquid introduction port toward an air vent,
a first electrode formed on the substrate and having a first end located in the capillary,

Serial No.: 10/533,601
Examiner: Hosein Kafinosavi
Reply to Office Action Mailed June 11, 2008
Page 5 of 8

a second electrode formed on the substrate and having a second end located in the capillary downstream from the first end of the first electrode with respect to a flow direction of the sample liquid, and

a window formed in the cover for checking whether the sample liquid is supplied into the capillary,

wherein the window has a downstream edge located downstream from the second end of the second electrode to check whether the sample liquid is supplied beyond the second end of the second electrode.